

Publish to Google Cloud Search for Developers

The following information is intended to assist with detailed developer tasks.

Publish to Google Cloud Search App Bundle

The Publish Google Cloud Search publisher ingests and publishes content from multiple unstructured and structured enterprise sources into GCS.

Publish to GCS App Bundle	
Factory Name	com.searchtechnologies.aspire:aspire-gcs-publisher-source
Inputs	AspireObject from a connector's subjob with metadata and content extracted from a specific file/folder. See Publish to Google Cloud Search How to Configure .
Type Flags	job-input

Configuration

Example Configuration File

```
<application config="com.searchtechnologies.aspire:aspire-gcs-publisher-
source:3.3" name="/Publish_to_GCS">
  <properties>
    <property name="sourceId">aab2effgfhg64ffcb1a5fgrbl2ebd7a9e6048<
/property>
    <property name="identitySourceId"
>aab2efgfec64ffgfhfla8ad1e0a236b2d4ba</property>
    <property name="streamVsBatch">BATCH</property>
    <property name="debug">>false</property>
    <property name="keyFile">/home/ secret_file.json</property>
    <property name="contentFormat">TEXT</property>
    <property name="useAsync">>true</property>
    <property name="rootUrl">https://cloudsearch.googleapis.com</property>
    <property name="emailGSuitePrincipal">>false</property>
    <property name="retryDelay">15</property>
    <property name="retryDelayMultiplier">2</property>
    <property name="retries">3</property>
    <property name="aclInheritanceType">NOT_APPLICABLE</property>
    <property name="maxRetryDelay">10</property>
    <property name="readTimeout">120</property>
    <property name="indexerType">clientlib-v1</property>
    <property name="documentHierarchy">>false</property>
    <property name="connectionTimeout">120</property>
  </properties>
</application>
```