

# Worker Node API



## Internal API

This is an internal API used for communication between nodes and is not expected to be used by others

The worker node API provides functionality that allows a manager and worker nodes to communicate.

## Release one or more seeds

Releases all the items currently not being processed, setting their status to be available, so the worker node stops processing a seed promptly when that seed is paused/stopped, this endpoint need the at least the **ADMINISTRATOR** or **MANAGER** role to be executed.

```
PUT /aspire/_api/worker/release/seed/:id
PUT /aspire/_api/worker/release/seed
```

### Path and Request Body Parameters

Name	Type	Required	Description
id	string	Required	The identifier(s) of the seed to be released

### Examples

Release a single seed

```
PUT /aspire/_api/worker/release/seed/AAABcID5GBc=
PUT /aspire/_api/worker/release/seed
{
  "id": [ "AAABcID5GBc=" ]
}
```

Release multiple seeds

```
PUT /aspire/_api/worker/release/seed
{
  "id": [ "AAABcID5GBc=", "AAABcIueWUc=" ]
}
```

### Response

```
{
  "message": "optional response message"
}
```

Status: 200, 404

## Throttle notification (Aspire 5.3)

Releases all the items currently not being processed, setting their status to be available, this endpoint need the at least the **ADMINISTRATOR** or **MANAGER** role to be executed.

```
PUT /aspire/_api/worker/throttle/:seedId
```

### Path and Request Body Parameters

Name	Type	Required	Description
seedId	string	Required	The identifier(s) of the seed to be released

#### Examples

```
PUT /aspire/_api/worker/throttle/AAABcID5GBc=
```

#### Response

```
{  
  "message": "optional response message"  
}
```

**Status:** 200, 404